



FINANCIERA MADERERA S.A. (FINSA)
N-550, KM 57
15890 SANTIAGO DE COMPOSTELA
(A CORUÑA)
SPAIN

DECLARATION OF PERFORMANCE N° 08007



15/07/2021

FINFLOOR SUPREME

Manufactured at: Finsa
Fibranor
Políg. Ind. de Rábade
27370 RÁBADE (ESPAÑA)

PRODUCT TYPE	INTENDED USE	AVCP*	NOTIFIED BODY AND REFERENCE
LAMINATED FLOORING	Floor covering for indoor applications	3	EPH - 0766

*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011

FINFLOOR SUPREME

CLASSIFICATION ACCORDING TO EN 685

Rev: 03/02/2014

CARACTERISTIQUES	SYMBOL	REQUIREMENT	TEST METHOD
Formaldehyde emissions HCHO		E1≤0.124mg/m3 (EN 717-1)	EN 14041 / EN 717-1 / EN 717-2
Reaction to fire		Bfl s1	EN 14041 / EN 13501-1 / EN ISO 9239-1 / EN ISO 11925-2
Slip resistance coefficient under dry conditions		Class DS (>=0,3)	EN 14041 / EN 13893
Electrical behaviour		The measurement of the body voltage at 23°C/25% humidity are =<2kV. Fulfils the criterions for the classification as an Antistatic Floor Covering	EN 14041 / EN 1815
Electrical behaviour / vertical resistance		Antistatic Floor "ASF – Class 2" in accordance with the international standard IEC 61340-4- 1:1995	EN 14041 / EN 1815
Thermal Resistance		Without Underlay: 0,06 m ² ·K/W + FINfloor PE Underlay 0,154 m ² ·K/W + Finfloor Silent Underlay 0,127 m ² ·K/W Suitable for warm-water underfloor heating systems	EN 14041 / EN 12664
Antibacterial efficiency		Reduction of bacterial activity in 24 hours ≥ 99.9% according to tests carried out at the IMSL	ISO 22196

CE Certificate



DoP 08007

EN 14041

The above information is subject to modifications for the benefit of further improvements.

The performance of the reference product are in compliance with the performance declared above
This Declaration of Performance is issued under the sole responsibility of FINANCIERA MADERERA S.A. (FINSA)

Javier Portela
FINSA R&D + Quality Director

Santiago de Compostela 26/10/2018

